

ENERGY FOR YOU...



SK-038 42 Příbovce 343
Tel.: +421/43/42 94 466
Tel.: +421/43/42 94 916
Fax.: +421/43/42 94 026
E-mail: tts@tts-martin.sk
www.tts-martin.sk



Diesel engine LOMBARDINI

Base power range from 15,8kVA within 43,7kVA

Nominal speed / frequency: 3000min⁻¹ / 50Hz

Nominal voltage : 3x230V / 400V



| GENSET TYPE | STAND-BY POWER (LTP) (kVA / kW) | PRIME POWER (PRP) (kVA / kW) | ENGINE TYPE | INDUCTION | SPEED REGULATION | FUEL CONSUMPTION (PRP) (L/h) | FUEL TANK VOLUME (L) | BASE UNIT DIMENSIONS (L / W / H) (mm) | BASE UNIT WEIGHT (kg) | CANOPY TYPE | WEIGHT 100LWA (kg) | WEIGHT 90LWA (kg) |
|---------------|------------------------------------|---------------------------------|---------------|-----------|------------------|---------------------------------|-------------------------|--|--------------------------|-------------|-----------------------|----------------------|
| MP13 B | 17,4 / 13,9 | 15,8 / 12,6 | LDW 1003 FOCS | N | M | 4,6 | 50 | 1400/700/950 | 250 | A | 550 | 600 |
| MP20 B | 26,2 / 21 | 28,8 / 23 | LDW 1603 CHD | N | M | 8,1 | 50 | 1400/700/1000 | 340 | A | 640 | 690 |
| MP27 B | 37,8 / 30,2 | 34,4 / 27,5 | LDW 2204 CHD | N | M | 8,4 | 100 | 1400/700/1000 | 450 | B | 800 | 850 |
| MP38 B | 48 / 38,4 | 43,7 / 35,0 | LDW 2204T CHD | T | M | 12,3 | 100 | 1400/700/1000 | 465 | B | 815 | 865 |

Induction

N - natural
T - turbocharged
TA – turbocharged with intercooler

Option:

- version for dusty condition

Speed regulation

M – mechanical (4%)
E – electronic (0,25%)

Canopy type (mm) (L / W / H)

A – 2000mm / 800mm / 1140mm
B – 2400mm / 800mm / 1140mm

Option:

- genset in container
- retention bath for genset without canopy
- industrial exhaust silencer
- residential exhaust silencer
- fast trailer
- remote genset monitoring and control
- engine heater
- increased generator protection level IP45